

Specifications Porsche Cayman*

Body: Two seat Coupé; lightweight body in aluminium-steel construction with doors, boot and bonnet lids made of aluminium; two-stage driver and front passenger airbags; side and head airbags for driver and front passenger.

Aerodynamics: Drag coefficient C_d : 0.30
Frontal area A: 2.00 m²
 $C_d \times A$: 0.6

Engine: Water-cooled flat-six engine; aluminium engine block and cylinder heads; four overhead camshafts, four valves per cylinder, variable inlet valve timing and lift (VarioCam Plus); hydraulic valve lifter; direct petrol injection; one three-way catalytic converter per cylinder bank, each with two oxygen sensors; engine oil 10.1 litres; electronic ignition with solid-state ignition distribution (six active ignition modules); thermal management for coolant circulation; auto start/stop function.

Bore: 89 mm
Stroke: 72.5 mm
Displacement: 2,706 cm³
Compression ratio: 12.5:1
Engine power: 275 hp (202 kW) at 7,400/min
Max. torque: 290 Nm at 4,500/min – 6,500/min
Power output per litre: 101.6 hp/l (74.6 kW/l)
Maximum revs: 7,800/min
Fuel type: Super Plus
Electrical system: 12 Volt; alternator 2,100 W; battery 70 Ah, 450 A; electrical system recuperation.

* Specifications may vary according to markets

Specifications • Porsche Cayman

Power transmission: Engine and transmission bolted together to form a single drive unit; rear wheel drive; six-speed manual transmission; optional seven-speed Doppelkupplungsgetriebe (PDK)

Gear ratios	Manual transmission	PDK transmission
1 st gear	3.67	3.91
2 nd gear	2.05	2.29
3 rd gear	1.46	1.65
4 th gear	1.13	1.30
5 th gear	0.97	1.08
6 th gear	0.84	0.88
7 th gear	–	0.62
Reverse	3.33	3.55
Final drive ratio	3.89	3.25
Clutch diameter	240 mm	202 mm /153 mm

Suspension: Front axle: Strut suspension (MacPherson type, Porsche optimised) with wheel-guiding strut and wheels independently mounted on transverse and longitudinal control arms; twin-tube gas-pressure dampers; electro-mechanical power steering.

Rear axle: Wheels independently guided on transverse control arms with longitudinal control arms, tie rods and suspension struts (McPherson type, optimised to Porsche requirements); cylindrical coil springs with internal dampers; anti-roll bar.

Brakes: Dual-circuit brake system with separate circuits for front and rear axles; Porsche Stability Management (PSM); vacuum brake booster; brake assistant; electric duo-servo parking brake; auto-hold function.

Specifications • Porsche Cayman

Front axle: Four-piston aluminium monobloc brake callipers, perforated and internally ventilated brake discs with 315 mm diameter and 28 mm thickness.

Rear axle: Four-piston aluminium monobloc brake callipers, perforated and internally ventilated brake discs with 299 mm diameter and 20 mm thickness.

Wheels and tyres:	front	8 J x 18	with	235/45 ZR 18
	rear	9 J x 18	with	265/45 ZR 18

Weights:	Kerb weight, DIN	1,330 (1,360) kg
	Permissible gross weight	1,655 (1,685) kg

Dimensions:	Length	4,380 mm
	Width	1,801 mm
	Width with exterior mirrors	1,978 mm
	Height	1,294 mm
	Wheelbase	2,475 mm

Track width	front	1,526 mm
	rear	1,536 mm

Luggage comp. capacity	front	150 l
	rear	184 l

Fuel tank capacity	64 l
--------------------	------

Values in brackets refer to vehicles with PDK transmission

Specifications • Porsche Cayman

Performance:	Top speed	266 (264) km/h
	Acceleration:	
	0 – 100 km/h	5.7 (5.6) s
	(with Sport Plus and PDK*	5.4 s)
	0 – 200 km/h	21.0 (20.9) s
	(with Sport Plus and PDK*	20.6 s)
Consumption (NEDC):	Combined	8.4 (7.9) l/100 km
	Urban	11.8 (10.9) l/100 km
	Extra-urban	6.4 (6.2) l/100 km
CO₂ emissions:		195 (183) g/km
Emissions class:		Euro 6

Values in brackets refer to vehicles with PDK transmission

*In conjunction with the optional Sport Chrono package.

Revised: May 2014