## Technical Data Audi R8 Coupé 5.2 FSI quattro S tronic (449 kW) Status: June 2015

Program for Germany

| Engine / electronics   |   |
|--|---|
| Engine type  | V10 gasoline engine (90° V angle) with dry sump lubrication, gasoline direct injection, four valve technology, DOHC cylinder head   |
| Valve gear / number of valves per cylinder   | Continuous intake and exhaust camshaft adjustment, roller cam followers with hydraulic support element / 4  |
| Displacement in cc / bore x stroke in mm / compression   | 5204 / 84.5 x 92.8 / 12.7   |
| Max. power output in kW (hp) / at rpm  | 449 (610) / 8250  |
| Max. torque in Nm (lb-ft) / at rpm   | 560 (413.0) / 6500  |
| Mixture preparation  | Combined injection system: gasoline direct injection and manifold injection   |
| Exhaust emission control   | One primary catalytic converter and one main catalytic converter per cylinder bank  |
| Emissions class  | EU 6  |
| Alternator in A / battery in A/Ah  | 210 water-cooled / 420/75   |
| Start-stop system  | Switches the engine off if the vehicle is stationary and the brake is engaged.  |
| Drivetrain / transmission  |   |
| Drive type   | All-wheel drive, mechanical differential lock, traction control (ASR)   |
| Clutch   | Two electrohydraulically controlled multi-plate clutches in an oil bath   |
| Transmission type  | 7-speed S tronic  |
| Gear ratio in 1st gear / 2nd gear  | 3.133 / 2.588   |
| Gear ratio in 3rd gear / 4th gear  | 1.958 / 1.244   |
| Gear ratio in 5th gear / 6th gear  | 0.979 / 0.976   |
| Gear ratio in 7th gear / 8th gear  | 0.841 / -   |
| Reverse gear / final drive ratio   | 2.647 / I: 4.458 for reverse, 1st, 4th + 5th, II: 3.588 for 2nd, 3rd, 6th, + 7th  |
| Suspension / steering / brakes   |   |
| Front suspension   | Double-wishbone suspension  |
| Rear suspension  | Double-wishbone suspension  |
| Steering / steering ratio / turning circle in m (D102) (ft)  | Basic: electromechanical steering (EPS) with i = 15.7  Optional: dynamic steering (EPS with ADS) with speed-dependent power assistance/ 11.2 (36.7)   |
| Brake system   | 6-piston fixed caliper brakes at front, 4-piston fixed caliper brakes at rear; carbon<br>fiber-reinforced ceramic brake disks with specially developed cooling ducts,<br>ventilated, perforated and floating; electromechanical parking brake at the rear |
| Wheels / tires (basic)   | Front axle: 8.5Jx19 /245/35 R19 ZR 93 Y XL Rear axle: 11Jx19 /295/35 R19 ZR 102Y, both with lightweight forged aluminum wheels  |
| Performance / consumption / acoustics Top speed in km/h (mph)  | 330 (205.1)   |
| Acceleration, 0-100 km/h (0-62.1 mph) in s   | 3.2 (with sport tires 3.1)  |
| Fuel / octane value  | Super Plus / 98 RON   |
| Idling / drive-past exterior noise level in dB (A)   | 74  |
| Consumption / emissions (according to tire size) Tire category 1: 19-inch  |   |
| Fuel consumption: city / highway / combined, in I/100 km (US mpg)  | 17.5 (13.4) / 9.3 (25.3) / 12.3 (19.1)  |
| CO <sub>2</sub> mass emission city / highway / combined, in g/km (g/mi)  | 408 (656.6) / 219 (352.4) / 287 (461.9)   |
| Servicing / guarantee (Germany)  | . ()  |
| Service inspection after max. km (mi)  | According to service indicator up to 30,000 km (18,641.1) (max. 2 years)  |
| Vehicle / paint / rust perforation guarantee   | 2 years with unlimited mileage / 3 years / 12 years   |
| Insurance classification in Germany: third party / fully comprehensive / part-   | No details  |
| comprehensive  | No details  |
| Weights / loads  |   |
| Unladen weight according to EU (excluding driver) / (including driver) / gross weight limit in kg ( <i>lb</i> )                    | Unladen weight: 1555 <i>(34</i> 28.2)<br>Dry weight: 1454 <i>(3205.5)</i> / 1630 <i>(35</i> 93.5) / 1895 <i>(4177.8)</i>  |
|  |   |
| Axle load limit at front / rear in kg ( <i>lb</i> )  Trailer load limit on 8% / 12% gradient braked / unbraked in kg ( <i>lb</i> ) | 890 (1962.1) / 1100 (2 <b>4</b> 25.1)<br>- / - / -  |
| Trailer load limit on 8% / 12% gradient, braked / unbraked in kg (lb)  | -1-1-   |
| Roof load limit / permissible nose weight in kg (lb)   |   |
| Capacities   | 0.17 (0.7)  |
| Cooling system capacity (incl. heating) in I (US gal)  | 24.7 (6.5)  |
| Engine oil capacity (including filter) in I (US qt)  | 8.3 (8.8)   |
| Fuel tank capacity in I (US gal)   | Basic: 73 (19.3)<br>Optional: 83 (21.9)   |
| Body / dimensions  |   |
| Body type / number of doors / seats  | Coupé / 2 / 2   |
| Drag coefficient Cd / frontal area A in m² (sq ft)   | 0.36 / 2.01 (21.6)  |
| Length (L103) / width excluding mirrors (W103) / height (H101-M) in mm (ft)  | 4426 (14.5) / 1940 (6.4) / 1240 (4.1)   |
| _ , , , , , , , , , , , , , , , , , , ,  | Rear overhang: 782 mm (30.8)  |
|  | Front overhang: 994 mm (39.1)   |
| Wheelbase (L101) / track at front/rear (W101-1/W101-2) in mm (ft)  | 2650 (8.7) / 1638 (5.4) / 1599 (5.2)  |
| Luggage capacity in I (cu ft)  | 112 (4.0) / capacity behind the seats: 226 (8.0)  |